

Stay Ahead of Your WAN Solution

SD-WANSolution Brief

Improve your WAN quality while lowering networking costs



Zyxel Nebula SD-WAN solution

Today there are increasing amount of enterprises with branch offices that are consuming more WAN bandwidth as they are collaborating online applications such as: Skype, WebEx, and many more! As more Internet communication and cloud-based application are adopted, it becomes a critical challenge for how to efficiently optimize WAN bandwidth, manage Internet application usage, and secure the connection between Branches, HQ, and Clients. Here at Zyxel, we believe that this type of technology should be for everyone. We have taken this enterprise approach to develop and tailor a

solution to fit the SMB market as well as cater toward Enterprise clients. This approach will vastly improve reliability and performance over traditional VPN (Site to Site) networks. Combining the flexibility of cloud-based technology and its high-speed deployment benefit, Zyxel SD-WAN solution helps IT administrators simplify branch network deployment. Designed to optimize Internet connectivity and applications, the Zyxel SD-WAN also enables ZyWALL VPN Series to support online application growth, efficiency WAN bandwidth usage and increase network agility.

Challenges for SMBS

- Greater reliability on Cloud including private cloud
- Reliable Internet with low-latency
- Faster connectivity and WAN performance improvement
- Increased security with greater scalability and reduced costs (installation and ongoing connectivity)

Challenges for VARs & MSPs

- Maximise on what connectivity is available
- Get easier control over deployment and management
- Reduce complexity, especially routing
- Remove bottlenecks from clients' networks
- Simplify network diversity (LTE/VDSL/Leased Line)
- Gain control over traffic shaping of bandwidth and applications



What Nebula SD-WAN can do?

Nebula Orchestrator Management


Easily switch between standalone gateway mode and our SD-WAN cloud management platform with Nebula Orchestrator, obtain the benefit from a centralized management for site to site connectivity. Nebula Orchestrator will continually measure and monitor all connections to establish the best quality connection. If the best path is better on another connection, it will seamlessly move the connection to give clients the best experience. Remote control and monitoring function from Nebula Orchestrator gives you more flexibility and lowers operation costs. Multi-tier management structure consisting of three level topologies includes Group, Organization and Site, allow configuration functions at each level to automate and simply management.

Cost Effective

SD-WAN improves the performance without extra bandwidth investments along with rock solid reliability of WAN Internet connections so that costly frame relay or MPLS lines are not required.

Greater Agility

SD-WAN is quick to deploy whilst MPLS may take months to install. This means that SD-WAN is lowering the complexity of running a network while simultaneously improving agility and efficiency.



Nebula SD-WAN license & services

Zyxel VPN50/VPN100/VPN300 will be bundled with a free 1 year SD-WAN license. Full features of SD-WAN license include: Orchestrator (cloud or on-premise), Dynamic Path Selection, WAN Optimization, Zero Touch Provision, Auto-VPN, Monitoring (Statistics) and Log. Customers who have already purchased can also receive a free one year SD-WAN license by downloading the new firmware update. Businesses can renew the SD-WAN Pack after the bundled license expires, its adaptation has been answer for most Enterprise deployments to

not only improve site to site connectivity but also reduce overheads often associated with traditional methods like MPLS and T1 ISP services. Alternatively, those seeking orchestrated management without advanced SD-WAN can revert to the Management Pack License. This pack uses Nebula Orchestrator to deliver zero-touch provisioning, VPN, firewall, and more. This excludes some SD-WAN functionality and other features, such as Application Patrol and Content Filtering.

License Packs

Nebula Orchestrator	Nebula Orchestrator
Basic (Free)	Management
Yes	Yes
-	Yes
Email/APP	Email/APP/SMS
Yes	Yes
Yes	Yes
Every 10 min	Every 3 min (3 sec Live Mode)
7 days	13 months
1 day	30 days
	Basic (Free) Yes Email/APP Yes Yes Every 10 min 7 days

Key features of SD-WAN



Zero Touch Provisioning (ZTP)


Deploy new branch gateway in minutes, reducing operational time and expense.

Take the hassle out of remotely deploying gateways that often need more settings than other devices in their initial configuration. Setup the first network rule within Nebula Orchestrator and then distribute the network settings via our Zero Touch Provisioning (email, SMS or USB) to all subsidiaries/sites through the cloud.



WAN Optimization

WAN Optimization technology increases data transfer efficiencies across WAN, giving reliable WAN quality, optimizing WAN traffic to improve WAN performance between branch offices and corporate headquarters. Each Site to Site connection is optimized by utilising Zyxel's WAN Optimization and combines it with Application Intelligence engine, which identifies more than 3000 protocols and applications, prioritize application by behaviour and user expectation.





Dynamic Mesh VPN

Allow gateways to establish dynamic direct VPN tunnels when traffic flow requests are the bottlenecks in the network. Effortlessly create site-site and client-site VPNs with our Auto VPN (site-to-site; client-to-site) function. Simplify the deployment to client devices with our simple three step process to get remote users connected hassle free. Auto VPN utilizes the native clients on Windows, Mac OS and iOS devices, allowing for an effortless software free installation process for client to site connectivity.



Dynamic Path Selection

Dynamic Path Selection real-time monitors path quality and automatically route mission critical applications to best-quality transmission path, which based on detected network latency, jitter, and packet drop status.



Gain Control over Security

Manage security for all sites via organization profiles to simplify security across all your sites, including: Firewall Rules, Geo Enforcer, Content Filtering and Application Patrol.

• Geo Enforcer


Geo Enforcer is an up-to-date mapping, which identifies the incoming traffic of geographical regions by examining its IP address. Enabling you the ability to filter traffic to and from specific locations.

Content Filtering

We protect your business from undesirable access to malicious, hacked or inappropriate websites with technologies such as URL filtering, HTTPS domain filter, safe search and Geo IP blocking.

Application Patrol

Block external threats and manage traffic by applications. Prioritize, throttle and block applications to boost productivity and prevent bandwidth abuse.



SD-WAN supported hardware

VPN50

Includes 1 Year

Nebula Orchestrator SD-WAN & Security Services

O SD-WAN Interfaces

4 x LAN/DMZ (1 Configurable) 1 x WAN, 1 x SFP

VPN Throughput

150 Mbps

O SPI Firewall Throughput

800 Mbps



VPN100

Includes 1 Year

Nebula Orchestrator SD-WAN & Security Services

Q SD-WAN Interfaces

4 x LAN/DMZ (1 Configurable) 2x WAN, 1 x SFP

O SPI Firewall Throughput 2,000 Mbps

O VPN Throughput 500 Mbps



VPN300

Includes 1 Year

Nebula Orchestrator SD-WAN & Security Services

O SD-WAN Interfaces

7 x GbE (Configurable)

O SPI Firewall Throughput 2,600 Mbps

O VPN Throughput 1,000 Mbps



Feature matrix

Model		ZyWALL VPN50 (SBs)	ZyWALL VPN100	(SMBs)	ZyWALL VPN300	(SMBs)
Mode		Standalone	Nebula SD-WAN	Standalone	Nebula SD-WAN	Standalone	Nebula SD-WAN
				27X61		27XEL = -11 = -	
Interfaces		4 x LAN/DMZ (GbE), 1 x WAN (GbE), 1 x SFP		4 x LAN/DMZ (GbE), 2 x WAN (GbE), 1 x SFP		7 x GbE (Configurable), 1 x SFP	
Hardware Specifi	cations	1 / 01 1		1 % 01 1			
USB3.0 ports		1		2		2	
Console port		Yes (RJ-45)		Yes (DB9)		Yes (DB9)	
Rack-mountable		-		Yes		Yes	
System Capacity	& Performance*1						
SPI firewall through	ghput (Mbps)*2	800	800	2,000	2,000	2,600	2,600
VPN throughput (Mbps)*3	150	150	500	500	1,000	1,000
Max. TCP concurr	ent sessions*4	400,000	400,000	800,000	800,000	2,000,000	2,000,000
Max. concurrent l	PSec VPN tunnels*5	50	50	100	100	300	300
Concurrent SSL V (default/max.)*6	PN users	10/50	-	30/200	-	50/300	-
VLAN interface		8	64	16	64	64	64
Concurrent devic	•	64	-	200/300	-	500/800	-
WLAN Manageme							
	ber (default/max.)*6	4/36	_	4/68	_	-	-
Key Features							
VPN		IKEv2, IPSec, SSL, L2TP/IPSec	IPSec, L2TP/ IPSec	IKEv2, IPSec, SSL, L2TP/IPSec	IPSec, L2TP/ IPSec	IKEv2, IPSec, SSL, L2TP/IPSec	IPSec, L2TP/ IPSec
SSL (HTTPS) insp	ection	-	-	Yes	-	Yes	-
Appication Patro		-	Yes, (bundle 1 year License)	-	Yes, (bundle 1 year License)	-	Yes, (bundle 1 year License)
Content filtering	* 6 * 8	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)
Geo Enforcer*6		Yes, (bundle 1 year License)	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)	Yes, (bundle 1 year License)
EZ Mode		Yes	-	-	-	-	-
Hotspot Manager	nent *6	Yes		Yes		Yes	
Ticket printer sup		-		Yes (SP350E) /10	_	Yes (SP350E) /10	
Support Q'ty (ma Amazon VPC	•	Yes	_	Yes	_	Yes	_
Facebook WiFi		Yes		Yes		Yes	_
Device HA Pro*10		-	-	Yes		Yes	-
SD-WAN Features	<u>*</u> *11	_	-	163	_	163	_
Dynamic Path Se		_	Yes	_	Yes	_	Yes
WAN Optimizatio		_	Yes	_	Yes	_	Yes
Zero Touch Provis		_	Yes		Yes	_	Yes
Auto VPN	Site-to-Site	_	Yes	_	Yes	_	Yes
71440 7777	Client-to-Site	_	Yes	_	Yes	_	Yes
App Patrol		-	Yes	-	Yes	-	Yes
Content Filter		_	Yes	-	Yes	-	Yes
Geo Enforcer (Geo	oIP)	-	Yes	-	Yes	-	Yes
Management		-	Yes	-	Yes	-	Yes
Monitor/ Log Stor	age	-	Yes	-	Yes	-	Yes
Power Requireme	nts						
Power input		12 V DC, 2.0 A max	(.	12 V DC, 2.5 A max	ζ.	12 V DC, 4.17 A ma:	x.
Max. power consu	ımption (watt)	12	<u> </u>	13.3	·	24.1	·
Heat dissipation (BTU/hr)	40.92		45.38		82.23	
Physical Specific	ations						
Item	Dimensions	216 x 143 x 33/		272 x 187 x 36/		300 x 188 x 44/	
	(WxDxH)(mm/in.)	8.50 x 5.63 x 1.30		10.7 x 7.36 x 1.42		16.93 x 7.4 x 1.73	
	Weight (kg/lb.)	0.88/1.94		1.4/3.09		1.65/3.64	
Packing	Dimensions	276 x 185 x 98/		427 x 247 x 73/		351 x 152 x 245/	
	(WxDxH)(mm/in.)	10.87 x 7.28 x 3.86		16.81 x 9.72 x 2.87		13.82 x 5.98 x 9.65	
المماريط ما من	Weight (kg/lb.)	1.41/3.11		2.23/4.91		2.83/6.24	
Included accesso	ries	Power adapterRJ-45 - RS-232 c	able for consols	Power adapterRack mounting	Ŀi+	Power adapterPower cord	
		• RJ-45 - RS-232 C	able for collsole	(optional, by rec		 Rack mounting l 	cit
		0011110001011		(Optional, by 169	,,		

Feature matrix

Model Mode		ZyWALL VPN50 (SE	ZyWALL VPN50 (SBs)		ZyWALL VPN100 (SMBs)		ZyWALL VPN300 (SMBs)	
		Standalone N	Nebula SD-WAN	Standalone	Nebula SD-WAN	Standalone	Nebula SD-WAN	
		27/4CD				2798.		
Environmental S	Specifications							
Operating environment	Temperature	0°C to 40°C /32°F to 104°F		0°C to 40°C/32°F to 104°F		0°C to 40°C/32°F to 104°F		
	Humidity	10% to 90% (non-condensing)		10% to 90% (non-condensing)		10% to 90% (non-condensing)		
Storage	Temperature	-30°C to 70°C/-22°F to 158°F		-30°C to 70°C/-22°F to 158°F		-30°C to 70°C/-22°F to 158°F		
environment	Humidity	10% to 90% (non-condensing)		10% to 90% (non-condensing)		10% to 90% (non-condensing)		
MTBF (hr)	-	44000		529,688.2 529688.2				
Certifications								
EMC		FCC Part 15 (Class B), IC, CE EMC		FCC Part 15 (Class B), CE EMC		FCC Part 15 (Class A), CE EMC		
		(Class B), RCM, BSN	(Class B), RCM, BSMI (Class		(Class B), C-Tick (Class B), BSMI		(Class A), C-Tick (Class A), BSMI	
Safetv		BSMI, UL		LVD (EN60950-1)	, BSMI	LVD (EN60950-1)), BSMI	

Note:
*: The matrix with firmware ZLD 4.31 and OPAL BE 1.12 or later.
*1: Actual performance may vary depending on network conditions and activated applications.
*2: Maximum throughput based on RFC 2544 (1,518-byte UDP packets).
*3: VPN throughput measured based on RFC 2544 (1,424-byte UDP packets).
*4: Maximum sessions measured using the industry standard IXIA IxLoad testing tool.
*5: Including Gateway-to-Gateway and Client-to-Gateway.
*6: With Zyxel service license to enable or extend the feature capacity.
*7: This is the recommend maximum number of concurrent logged-in devices.
*8: SafeSearch function in Content Filtering need to enable SSL inspection firstly and not for small business.
*9: With Hotspot Management license support.
*10: ZyWALL VPN100 or above supports Device HA Pro once registered.
*11: After device upgrading firmware to SD-OS v10.01 and was transformed to SD-WAN mode.
*12: After upgrading firmware to SD-OS v10.02 or after.

Like us, follow us



Facebook

Post your questions to Facebook anytime. Support is available in English.

Q facebook.com/zyxel



YouTube

Watch video tutorials and learn how to setup with Zyxel security products.

Q youtube.com/zyxelvideo



LinkedIn

Post your questions to LinkedIn anytime. Support is available in English.

Q linkedin.com/company/zyxel



License Finder

Find out different services and licenses to meet your business needs.

Q zyxel.com/licensefinder



Forum

Post questions to our forum community and Zyxel officials. Submit ideas for future product features or releases!

Businessforum.zyxel.com



Zyxel Blog

Read articles and learn how to apply with Zyxel security products.

Q blog.zyxel.eu





Corporate Headquarters

Zyxel Communications Corp.

Fax: +886-3-578-2439 Email: sales@zyxel.com.tw http://www.zyxel.com

Europe

Zvxel Belarus

Tel: +375 17 334 6099 Fax: +375 17 334 5899 Email: sales@zyxel.by http://www.zyxel.by

Zyxel BeNeLux

Tel: +31 23 555 3689 Fax: +31 23 557 8492 Email: sales@zyxel.nl http://www.zyxel.be

Zyxel Bulgaria (Bulgaria, Macedonia, Albania, Kosovo)

Email: info@cz.zyxel.com http://www.zyxel.bg

Zyxel Czech Republic

Tel: +420 241 091 350 Hotline: +420 241 774 665 Fax: +420 241 091 359 Fmail: sales@cz zyxel.com http://www.zyxel.cz

Zyxel Denmark A/S

Fax: +45 39 55 07 07 Fmail: sales@zvxel dk http://www.zyxel.dk

Zyxel Finland

Tel: +358 9 4780 8400 Email: myynti@zyxel.fi http://www.zyxel.fi

Zyxel France

Tel: +33 (0)4 72 52 97 97 Fax: +33 (0)4 72 52 19 20 Email: info@zvxel.fr http://www.zyxel.fr

Zvxel Germany GmbH

Tel: +49 (0) 2405-6909 0 Fax: +49 (0) 2405-6909 99 Email: sales@zvxel.de http://www.zyxel.de

Zyxel Hungary & SEE

Tel: +36 1 848 0690 Email: info@zyxel.hu http://www.zyxel.hu

Zyxel Iberia Tel: +34 911 792 100 Email: ventas@zyxel.es http://www.zyxel.es

Tel: +39 011 2308000 Email: info@zyxel.it http://www.zyxel.it

Zvxel Norway

Tel: +47 22 80 61 80 Fax: +47 22 80 61 81 Email: salg@zyxel.no http://www.zyxel.no

Zyxel Poland

Tel: +48 223 338 250 Hotline: +48 226 521 626 Fax: +48 223 338 251 http://www.zyxel.pl

Tel: +40 31 0809 888 Fax: +40 31 0809 890 http://www.zyxel.ro

Zyxel Russia Tel: +7 (495) 539-9935 Fax: +7 (495) 542-8925 Email: info@zyxel.ru http://www.zyxel.ru

Zyxel Slovakia

Tel: +421 220 861 847 Hotline: +421 220 861 848 Fax: +421 243 193 990 Email: info@cz.zyxel.com http://www.zyxel.sk

Zyxel Sweden A/S

Tel: +46 8 55 77 60 60 Fax: +46 8 55 77 60 61 Email: sales@zyxel.se http://www.zyxel.se

Zyxel Switzerland

Tel: +41 (0)44 806 51 00 Fax: +41 (0)44 806 52 00 Email: info@zyxel.ch http://www.zyxel.ch

Zyxel Turkey A.S. Tel: +90 212 314 18 00 Fax: +90 212 220 25 26 Email: bilgi@zyxel.com.tr http://www.zvxel.com.tr

Tel: +44 (0) 118 9121 700 Fax: +44 (0) 118 9797 277 Email: sales@zyxel.co.uk http://www.zyxel.co.uk

Tel: +380 (50) 440 88 61 Email: evelichko@zyxel.eu http://www.zyxel.ua

Asia

Zvxel China (Shanahai) China Headquarters

Fax: +86-021-52069033 Email: sales@zyxel.cn http://www.zyxel.cn

Zyxel China (Beijing)

Email: sales@zyxel.cn http://www.zyxel.cn

Zyxel China (Tianjin)

Tel: +86-022-87890440 Fax: +86-022-87892304 http://www.zyxel.cn

Zyxel India Tel: +91-11-4760-8800 Fax: +91-11-4052-3393 Email: info@zyxel.in http://www.zvxel.in

Zvxel Kazakhstan

Tel: +7-727-2590-699 Fax: +7-727-2590-689 Email: info@zvxel.kz http://www.zyxel.kz

Zyxel Korea Corp.

Fax: +82-2-890-5537 Email: sales@zyxel.kr http://www.zyxel.kr

Zvxel Malaysia

Tel: +603 2282 1111 Fax: +603 2287 2611 Email: sales@zvxel.com.mv http://www.zyxel.com.my

Zvxel Middle East FZE

Tel: +971 4 372 4483 Cell: +971 562146416 Email: sales@zyxel-me.com http://www.zyxel-me.com The Americas

Email: sales@zyxel.com

http://us.zyxel.com

North America Headquarters Tel: +1-714-632-0882 Fax: +1-714-632-0858

Tel: +55 (11) 3373-7470 Fax: +55 (11) 3373-7510 Email: comercial@zyxel.com.br

http://www.zyxel.com/br/pt/

Zvxel USA

Zyxel Brazil

Zyxel Philippine

http://www.zyxel.com.ph

Zyxel Singapore

Tel: +65 6339 3218 Hotline: +65 6339 1663 Fax: +65 6339 3318 Email: sales@zyxel.com.sg http://www.zyxel.com.sg

Zyxel Taiwan (Taipei)

Fax: +886-2-2735-3220 Email: sales_tw@zyxel.com.tw http://www.zyxel.com.tw

Zyxel Thailand

Tel: +66-(0)-2831-5315 Fax: +66-(0)-2831-5395 Email: info@zvxel.co.th http://www.zyxel.co.th

Zyxel Vietnam

Tel: (+848) 35202910 Fax: (+848) 35202800 Email: sales_vn@zyxel.com.tw http://www.zyxel.com/vn/vi/

For more product information, visit us on the web at www.zyxel.com

Copyright © 2019 Zyxel Communications Corp. All rights reserved. Zyxel, Zyxel logo are registered trademarks of Zyxel Communications Corp. All other brands, product names, or trademarks mentioned are the property of their respective owners. All specifications are subject to change without notice.

