

# The All-in-one Guest Access Solution of **Tomorrow, Delivered Today**





Providing Internet access in hospitality venues is not the same as in homes or offices as users come and go in large numbers, making access management and bandwidth abuse prevention exceptionally challenging; and convenient, always online and high-quality WLAN connectivity are necessary for customer satisfaction as well. To address this, ZyXEL offers comprehensive Unified Access Gateway (UAG) portfolio to help hospitality organizations for:



#### **Lowered TCO**

- Services provided through an one-box device
- Scale up concurrent login numbers and managed APs without the need for hardware upgrades



# **Revenue generation**

- Advanced billing feature offers flexible free, paid and tiered Wi-Fi services
- Billing plans can be customized to suit different needs



# **Higher customer satisfaction**

- Non-stop Internet uptime with dual-WAN support
- Concurrent 2.4 GHz and 5 GHz Wi-Fi bands with combined rates of up to 600 Mbps



# Secured network connectivity

- Built-in firewall provides secured network services for both customers and the staff
- Works with Unified Security Gateway (USG) for advanced network security






# **Application Diagram**

# **Instant hotspot solution**


- Concurrent 2.4 GHz and 5 GHz Wi-Fi bands\* provide 2x the spectrum and 2x the bandwidth to accommodate a much larger amount of wireless devices
- The combination of ZyXEL UAG and SP350E enables one-click billing and account generation with voucher ticketing to offer easy operation for staff members and smooth services flows in busy cafés
- Supports SMS ticketing to deliver account information directly to the customers' mobile phones
- Traffic logs can be stored in remote syslog servers or local USB dongles
- \* Concurrent 2.4 GHz and 5 GHz Wi-Fi bands support on UAG2100/4100



# **Facilitating client-to-site connection**

# VPN 1-to-1 mapping


- Resolves IP conflicts when more than one user connect to the same remote VPN gateway via client-to-site VPN tunnels
- Makes the IP addresses of the computers appear to be different
- Enables multiple business travelers to connect to their offices via VPN at the same time






#### Comprehensive alternatives for free or paid Internet access

- ZyXEL UAG billing plans can be customized with varying bandwidth speeds, service durations and levels of payments
- Voucher ticketing can generate accounts easily with the combination of ZyXEL UAG and SP350E ticket printers at the counter
- Supports SMS ticketing to deliver account information directly to the customers' mobile phones
- Customers gain access to the Internet upon accepting the customized user agreement page
- Online ticketing with Paypal is also supported for more flexibility



# Flexible deployment

- With ZyXEL UAG, clients can ensure secure access to cloud applications and remote administration privileges
- Dual-WAN\* support assures continuous business
- Built-in WLAN controller for scalable Wi-Fi coverage extension and management






# **Unified Access Gateway Series Application Guide**

#### **Total security**

- Works with the ZyXEL Unified Security Gateway (USG) to provide advanced network protection
- The UAG automatically record user account information, MAC addresses, source and destination IPs, data volume and protocol types for future auditing
- Enables businesses to protect personal devices connected to the Web through both wired and wireless from anonymous hacking attempts by L2 isolation





# **Unified Access Gateway Series Application Guide**

# **Portfolio**

Product photo	Model Name	UAG5100	UAG4100	UAG2100
Hardware Specifications	Model Name	0A03100		5AG2100
19/10/1000 Mbps RI-45 ports	Product photo	-0-11 ******		11 2 1135
19/10/1000 Mbps RI-45 ports	Hardware Specifications			
USB ports	·	3 x LAN, 2 x WAN	4 x LAN, 1 x WAN	4 x LAN, 1 x WAN
Tikket printer support   Yes (SP350E)   Yes (Yes (Yes (SP350E)   Yes (Yes (SP350E)   Yes (Yes (Yes (Yes (SP350E)   Yes		,		
System Capacity & Performance*	-			
Routing throughput (Mbps) 2		133 (3. 33.32)	100 (0.0002)	133 (5. 53 52)
Concurrent logins (default/max.)   500/800   200/300   100/200		250	200	150
Max. concurrent sessions				
DHCP pool size				<del>                                     </del>
Wiley   War   Wa	DHCP pool size	,	,	<del>'</del>
Suit-in WLAN controller	WLAN Management			
Managed AP number (default/max.)	Built-in WLAN controller	Yes	Yes	Yes
SSID	Managed AP number (default/max.)			
Standard compliance   -   802.11 a/b/g/n   802.11 a/b/g/n   Radio   -   2   2   2   2   2   2   2   2   2	SSID		-	+
Standard compliance   -	Wireless Specifications			
Antennas	Standard compliance	-	802.11 a/b/g/n	802.11 a/b/g/n
WAN   WAN load-balancing/failover   Yes/Yes   -/-   -/-   -/-   AAA & Billing   Web-based authentication   Yes	Radio	-	-	
WAN load-balancing/failover   Yes/Yes   -/-   -/-   AAA & Billing   Wab-based authentication   Yes	Antennas	-	2.4 GHz: 2T2R MIMO; 5 GHz: 2	T2R MIMO (Detachable, SMA-R)
Web-based authentication   Yes   Y	WAN			
AAA & Billing   Web-based authentication   Yes   Yes   Yes   Yes   RABDIUS client   Yes   Yes	WAN load-balancing/failover	Yes/Yes	-/-	-/-
Yes   Yes	AAA & Billing			
Time-to-finish/Accumulation billing modes   Yes/Yes   Yes   Yes	Web-based authentication	Yes	Yes	Yes
Yes   Yes	RADIUS client	Yes	Yes	Yes
Yes   Yes	Time-to-finish/Accumulation billing modes	Yes/Yes	Yes/Yes	Yes/Yes
Yes   Yes   Yes   Yes   Yes   Yes   Yes   Yes   SMS ticketing   Yes   Yes   Yes   License	Customizable billing profiles	Yes	Yes	Yes
Yes   Yes   License	Account operator	Yes	Yes	Yes
Yes   Yes	User agreement	Yes	Yes	Yes
Yes   Yes	SMS ticketing	Yes	Yes	License
Yes   Yes	Security			
Yes   Yes	SPI firewall			
PSec VPN	Layer 2 isolation		Yes	Yes
Yes   Yes	VPN pass-through			Yes
Yes		` ,		
Yes   Yes		Yes	Yes	Yes
Yes (read only)   Yes (read			.,	
Yes   Yes				+
Pass-through address         Yes (IP)         Yes (IP)         Yes (IP)           Walled garden         Yes         Yes         Yes           Customizable login page         Yes         Yes         Yes           Customizable user agreement page         Yes         Yes         Yes           Power Requirements         Yes         Yes         Yes           Power input         100 - 240 V AC, 0.6 A         12 V DC, 3 A max.         12 V DC, 3 A max.           Max. power consumption (watt)         25         28         28           Included accessories         • Power cord • Rack mounting kit • Antenna         • Power adapter • Rack mounting kit • Antenna         • Antenna           Physical Specifications         382 x 205 x 44/ 15.04 x 8.07 x 1.73         272 x 171 x 36/ 10.71 x 6.73 x 1.42         272 x 171 x 36/ 10.71 x 6.73 x 1.42		•	1	
Walled garden         Yes         Yes         Yes           Customizable login page         Yes         Yes         Yes           Customizable user agreement page         Yes         Yes         Yes           Power Requirements         Yes         Yes         Yes           Power input         100 - 240 V AC, 0.6 A         12 V DC, 3 A max.         12 V DC, 3 A max.           Max. power consumption (watt)         25         28         28           Included accessories         • Power cord • Rack mounting kit • Antenna         • Power adapter • Rack mounting kit • Antenna         • Antenna           Physical Specifications         382 x 205 x 44/ 15.04 x 8.07 x 1.73         272 x 171 x 36/ 10.71 x 6.73 x 1.42         272 x 171 x 36/ 10.71 x 6.73 x 1.42				<del> </del>
Customizable login page         Yes         Yes         Yes           Customizable user agreement page         Yes         Yes         Yes           Power Requirements         Yes         Yes         Yes           Power input         100 - 240 V AC, 0.6 A         12 V DC, 3 A max.         12 V DC, 3 A max.           Max. power consumption (watt)         25         28         28           Included accessories         • Power cord • Rack mounting kit • Rack mounting kit • Antenna         • Rack mounting kit • Antenna         • Rack mounting kit • Antenna           Physical Specifications         382 x 205 x 44/ 15.04 x 8.07 x 1.73         272 x 171 x 36/ 10.71 x 6.73 x 1.42         272 x 171 x 36/ 10.71 x 6.73 x 1.42				
Customizable user agreement page         Yes         Yes         Yes           Power Requirements         100 - 240 V AC, 0.6 A         12 V DC, 3 A max.         12 V DC, 3 A max.           Max. power consumption (watt)         25         28         28           Included accessories         • Power cord • Rack mounting kit • Antenna         • Rack mounting kit • Antenna         • Rack mounting kit • Antenna           Physical Specifications         382 × 205 × 44/ 15.04 × 8.07 × 1.73         272 × 171 × 36/ 10.71 × 6.73 × 1.42         272 × 171 × 36/ 10.71 × 6.73 × 1.42				+
Power Requirements	5 . 5		i e	
Power input		ies	ies	res
Max. power consumption (watt)         25         28         28           Included accessories         • Power cord • Rack mounting kit • Rack mounting kit • Antenna         • Power adapter • Rack mounting kit • Antenna         • Power adapter • Rack mounting kit • Antenna           Physical Specifications         382 x 205 x 44/ 15.04 x 8.07 x 1.73         272 x 171 x 36/ 10.71 x 6.73 x 1.42         272 x 171 x 36/ 10.71 x 6.73 x 1.42	-	100 - 240 \ AC 0.6 A	12 V DC 2 A may	12 V DC 2 A may
Power cord • Power adapter • Rack mounting kit • Antenna • Power adapter • Rack mounting kit • Antenna • Power adapter • Rack mounting kit • Antenna • Power adapter • Rack mounting kit • Antenna • Antenna • Physical Specifications  Dimensions (WxDxH)(mm/in.) 382 × 205 × 44/ 272 × 171 × 36/ 10.71 × 6.73 × 1.42 10.71 × 6.73 × 1.42	-	,		
Physical Specifications  382 x 205 x 44/ 272 x 171 x 36/ 15.04 x 8.07 x 1.73  272 x 171 x 36/ 10.71 x 6.73 x 1.42  272 x 171 x 36/ 10.71 x 6.73 x 1.42	Included accessories	• Power cord	Power adapter     Rack mounting kit	Power adapter     Rack mounting kit
Dimensions (WxDxH)(mm/in.) 382 x 205 x 44/ 272 x 171 x 36/ 15.04 x 8.07 x 1.73 10.71 x 6.73 x 1.42 272 x 171 x 36/ 10.71 x 6.73 x 1.42	Physical Specifications			
Weight (kg/lb.) 2.36/5.20 1.46/3.22 1.46/3.22	Dimensions (WxDxH)(mm/in.)		272 x 171 x 36/ 10.71 x 6.73 x 1.42	272 x 171 x 36/ 10.71 x 6.73 x 1.42
	Weight (kg/lb.)	2.36/5.20	1.46/3.22	1.46/3.22













<sup>\*1:</sup> Actual performance may vary depending on network conditions and activated applications.
\*2: Routing throughput measured using the industry standard IXIA IxLoad testing tool (1,460-byte TCP packets).
\*3: Maximum sessions measured using the industry standard IXIA IxLoad testing tool.